



Sage Oil Vac

Manufacturers of on-site maintenance equipment



TRAILERS

VERSATILE • DEPENDABLE • PRACTICAL

TOLL FREE **877-OIL-VACS** • www.sageoilvac.com

Trailer Model



Tanks gallons / (liters)	10080	10083	10120	10250	10253	11120	11186
Length ft / (m)	TWO 80 / (303) 12'2" / (3.71)	ONE 60 / (227) TWO 80 / (303) 14'1" / (4.27)	TWO 120 / (454) 13'9" / (4.19)	TWO 250 / (946) 15'10" / (4.83)	ONE 120 / (454) TWO 250 / (946) 18' / (5.49)	ONE 120 / (454) FOUR 60 / (227) 15'6" / (4.72)	TWO 220 / (832) FOUR 120 / (454) 19'6" / (5.94)
Width ft / (m) (outside fender to outside fender)	6' / (1.83)	6' / (1.83)	7' / (2.13)	7' / (2.13)	7' / (2.13)	7' / (2.13)	7' / (2.13)
Empty Weight lb / (kg)	1520 / (690)	1820 / (825)	2165 / (982)	2700 / (1225)	3220 / (1460)	4300 / (1950)	7550 / (3425)
Normal Operating Weight lb / (kg) ¹	2104 / (954)	2623 / (1189)	3041 / (1379)	4525 / (2052)	5483 / (2487)	5614 / (2546)	10908 / (4948)
Max Weight lb / (kg) ²	2888 / (1219)	3426 / (1554)	3917 / (1776)	6350 / (2880)	7746 / (3513)	6665 / (3023)	13594 / (6166)
Tire Size	15"	15"	15"	15"	15"	15"	16"
Reel Cabinet	O	O	O	O	O	O	S
Epoxy-lined Coolant Tanks	N/A	N/A	N/A	N/A	N/A	(1) 60g	(1) 120g
Coupler	2" - U	2" - U	2" - U	2" - U	2" - U	2.5 / 6" - U	2.5 / 6" - U
Compressor HP	55 HP	55 HP	55 HP	55 HP	55 HP	8 HP	13 HP
CFM @ 40PSI	12.5	12.5	12.5	12.5	12.5	18.5	20
Air Reel	O	O	O	O	O	S	S
Spare Tire	O	O	O	O	O	S	S
Hose Length ft / (m)	25 / (7.62)	25 / (7.62)	25 / (7.62)	50 / (15.24)	50 / (15.24)	50 / (15.24)	50 / (15.24)

¹ Assumes all fluid tanks are half full

² Assumes all fluid tanks are 90% full

O - Optional Equipment

S - Standard Equipment

U - Universal

Equipment shown is for illustrative purposes and may display optional accessories or components. Sage Oil Vac reserves the right to make changes in engineering, design or specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. © 2011 Sage Oil Vac Inc. All Rights Reserved.

Sage Oil Vac Inc.
360 N. Lakeside Drive
Amarillo, TX 79118
Phone: (806) 372-7559
Fax: (806) 372-7565
www.sageoilvac.com
Call toll-free 1-877-OILVACS
(1-877-645-8227)



Used Filter Receptacle™

(patent #5884676)
The Used Filter Receptacle™ provides a convenient location to drain, store and transport used oil filters from the service site to the disposal site. Accumulated oil is vacuumed into the used oil tank.



Filter Stinger™

(patent #5476154)
Use the Filter Stinger™ to puncture and empty the used oil filter before it is spun off. The Filter Stinger™ reduces messy drips and hot oil burns.



Barrel Straw

Attach the Barrel Straw to the fresh fluid tank and insert the opposite end in a bulk tank to vacuum fresh fluids in to the fluid tank. Fresh fluids may be vacuumed at rates of 10 to 20 gallons per minute.

Note: Tanks may be filled by pouring into the top.



Drain Pan

All drain pans come with the ability to quick connect to the Sage Oil Vac equipment. Drain pans are available in 10 or 17 gallon capacities.



Quick Disconnect Fittings

Outfit equipment with Quick Disconnect Fittings to vacuum used oil directly from the crankcase in to the used oil tank. Hot oil changes may be done 60% faster than gravity drains.