

SAGE OIL VAC JOBSITE TRAILER

MODEL 1E6J-6



TANKS

- (1) 220 gallon (833 I)ASME tank used oil
- (1) 220 gallon (833 I)ASME tank fresh oil & fluid
- (3) 120 gallon (454 I)ASME tank fresh oil & fluid
- (1) 120 gallon (454 I)ASME EPOXY tank- Fresh Coolant
- 120 lb greae keg holder with 50:1 Alemite piston pump

POWER

• 24 CFM vacuum/compressor driven by 13 hp electric start Honda gas engine – 125 psi max

HOSES & REELS

- (1) 1 in x 50 ft (2.54 cm x 15.2 m) used oil hose on spring retractable reel
- (4) 3/4 in x 50 ft (1.905 cm x 15.2 m) fresh oil hose on spring retractable reel
- (1) 5/8 in x 50 ft (1.59 cm x 15.2 m) coolant/antifreeze hose on spring retractable reel
- 3/8 in x 50 ft (0.9525 cm x 15.2 m) air hose on spring retractable reel
- 3/8 in x 50 ft (0.9525 cm x 15.2 m) grease hose on spring retractable reel



SAGE OIL VAC ATTRIBUTES

- Patented vacuum process to load fresh fluid tanks (Barrel Straws priced separately specify quantity and length)
- Patented used Filter Receptacle
- Patented Filter Stinger (priced separately)
- 25 micron filters on all new oil reels

HOSE ENDS, METERS, HANDLES

- Used oil hose 1 in (2.54 cm) cam and groove fitting
- Fresh fluid hoses 1/2 in (1.27 cm) flush face quick disconnects, adaptable to meters (priced separately, specify quantity and type)
- Diesel Dispensing Nozzle on Diesel Reel
- DEF Nozzle

FRAME

- Trailer mounted
- Tandem 7000 lb leaf spring axle with electric brakes
- (4) 225/75R17.5 tires
- (1) 225/75R17.5 Spare Tire with Bracket
- Universal 2 5/16 in hitch
- Drop leg jack
- Tongue-mounted toolbox- Large Cabinet
- DOT-approved light package
- 7 plug electric adapter
- Rear Reel Cabinet W/ Dust Proof Lockable Roll-up Shutter Style Door

DIMENSION & WEIGHTS

Width: 95 in (2.41 m)Length: 259.8 in (6.6 m)

• Empty weight: 7550 lb (3425 kg)

Normal max operating weight: 12660 lb (5742 kg)