



SAGE OIL VAC **JOBSITE TRAILER**

MODEL 1C5G-5100

Sage Oil Vac made the 1C5G-5 jobsite trailer extremely versatile with its towable capabilities. This unit features four fresh product tanks, open reels and valuable storage space.



TANKS

- (1) 120 gallon (454 l) ASME tank used oil
- (3) 60 gallon (227 l) ASME tank fresh oil & fluid
- (1) 60 gallon (227 l) ASME EPOXY fresh coolant

POWER

- 22 CFM vacuum/compressor driven by 8 hp electric start Honda gas engine – 125 psi max



HOSES & REELS

- (1) 1 in in x 50 ft (2.54 cm x 15.2 m) used oil hose on spring retractable reel
- (3) 3/4 in x 50 ft (1.905 cm x 15.2 m) fresh oil hose on spring retractable reel
- (1) 5/8 in x 50 ft (1.5875 cm x 15.2 m) fresh coolant on spring retractable reel
- (1) 3/8 in x 50 ft (0.9525 cm x 15.2 m) air hose on spring retractable reel

SAGE OIL VAC ATTRIBUTES

- Patented vacuum process to load fresh fluid tanks (Barrel Straws priced separately — specify quantity and length)
- Patented used Filter Receptacle
- Patented Filter Stinger (priced separately)
- 25 micron filters on all new oil reels

HOSE ENDS, METERS, HANDLES

- Used oil hose — 1 in (2.54 cm) cam and groove fitting
- Fresh fluid hoses — 1/2 in (1.27 cm) flush face quick disconnects, adaptable to meters (priced separately, specify quantity and type)

FRAME

- Trailer Mounted
- Tandem 5200 lb leaf spring axle with electric brakes
- (4) 225/75R15 tires
- Universal 2 5/16 in hitch
- Drop leg jack
- Tongue-mounted toolbox (24 in W x 16 in D x 43 in H)
- DOT-approved light package
- 7 plug electric adapter

DIMENSION & WEIGHTS

- Width: 86 in (2.18 m)
- Length: 208.25 in (5.28 m)
- Empty weight: 4300 lb (1950 kg)
- Normal max operating weight: 6052 lb (2745 kg)