

SAGE OIL VAC SERVICE SKIDS

MODEL 2M36-2102

The 2M36-2102 service skid provides great value to the jobsite. This two-tank system is typically used for basic oil changes ans servicing when only one type of new oil is needed. Each tank holds up to 60 gallons each. This skid also comes without a compressor so you can utilize the compressor on your current service body.



TANKS

- (1) 60 gallon (227 I)ASME tank used oil
- (1) 60 gallon (227 I)ASME tank fresh oil & fluid

POWER

- Additional Air Source Required
- Vacuum Generator for Vacuum Assist



HOSES & REELS

- (1) 3/4 in in x 25 ft (1.905 cm x 7.6 m) used oil hose on spring retractable reel
- (1) 5/8 in x 25 ft (1.905 cm x 7.6 m) fresh oil hose on spring retractable reel
- · Integrated used oil offload

SAGE OIL VAC ATTRIBUTES

- Patented vacuum process to load fresh fluid tanks (Barrel Straws priced separately specify quantity and length)
- Patented used Filter Receptacle
- Patented Filter Stinger (priced separately)
- 25 micron filters on all new oil reels

HOSE ENDS, METERS, HANDLES

- Used oil hose 3/4 in (1.905 cm) cam and groove fitting
- Fresh fluid hoses 1/2 in (1.27 cm) flush face quick disconnects, adaptable to meters (priced separately, specify quantity and type)

FRAME

- Skid mounted
- Table top frame design
- Forklift-able (empty only)

DIMENSION & WEIGHTS

- Width: 44.5 in (1.13 m)
- Length: 73.38 in (1.86 m)
- Height: 45.38 in (1.15 m)
- Empty weight: 950 lb (430.9 kg)
- Normal max operating weight: 1390 lb (630.5 kg)