



SAGE OIL VAC **FLUSH AND RINSE UNITS**

MODEL 7H8N-4

The 7H8N-4 GOEX unit has all the features of the 1E6M-4 open style trailer only in an enclosed cargo trailer. This trailer is insulated and heated- it's perfect for cold weather climates and performing oil changes in less-than ideal conditions. Like the 1E6M-4, this unit includes four tanks: one for used product, one for final-fill oil and the remaining two are rinse and flush tanks.



TANKS

- (1) 390 gallon (1476.31 l)ASME tank used oil
- (1) 390 gallon (1476.31 l)ASME tank fresh oil & fluid
- (1) 120 gallon (454 l) ASME tank- flush oil
- (1) 120 gallon (454 l) ASME tank- rinse oil

POWER

- 22 CFM vacuum/compressor driven by 8 hp electric start Honda gas engine – 125 psi max
- 1000 PSI, 8 GPM fluid pumps driven by 5.5 HP Honda Engine

HOSES & REELS

- (1) 1 in x 330 ft (2.54 cm x 100.5 m) used oil hose on spring retractable reel
- (1) 3/4 in x 330 ft (1.905 cm x 100.5 m) fresh oil hose on spring retractable reel fresh and used oil hoses paired on single air rewind reel
- 3/4 in x 300 ft (1.905 cm x 100.5 m) flush & rinse oil hose- mounted on air rewind reel
- (optional) air rewind reel upgrade (Priced Separately)



SAGE OIL VAC ATTRIBUTES

- Patented vacuum process to load fresh fluid tanks (Barrel Straws priced separately)
- 1GPM Filtration Unit- Filters Fresh Oil to 3 Microns
- Fluid Heat System- Shell and tube heat exchangers
- Propane fired tank-less hot water heater
- Up-tower meter, magnet, and 5 micron filter assembly
- Up-tower used oil assist pump, 1 hp, 110 vac, 15 amp
- Rinse and flush oil tank use same reel and pump
- (optional) dual Y2K 4 micron flush/rinse filter system (priced separately)

HOSE ENDS, METERS, HANDLES

- Used oil hose — 1 in (2.54 cm) cam and groove fitting
- Fresh fluid hoses — hard plumbed to meters
- (2) digital in-line 1000 psi fluid meters

FRAME

- Trailer mounted
- Tandem 7000 lb leaf spring axle with electric brakes
- Universal 2 5/16 in hitch
- DOT-approved light package
- 7 plug electric adapter
- Escape door on passenger side
- Spare tire included
- Adjustable hitch
- Skid installed onto rubber mat
- Double back doors
- Secondary containment system 430 gallon (1628 l) minimum capacity, drain capability at both ends of containment

DIMENSION & WEIGHTS

- Width: 100 in (2.54 m)
- Length: 358 in (9 m)
- Empty weight: 13395 lb (6076 kg)
- Normal max operating weight: 17118 lb (7765 kg)