



SAGE OIL VAC **JOBSITE TRAILER**

MODEL 7C7F-5100

The 7C7F-5100 jobsite trailer is the enclosed version on the 1C5G-5100 jobsite trailer. This unit features three fresh product tanks, one fresh coolant tank, Reel Cabinet and valuable storage space.



TANKS

- (1) 120 gallon (454 l) ASME tank used oil
- (3) 60 gallon (226 l) ASME tank fresh oil & fluid
- (1) 60 gallon (226 l) ASME EPOXY tank- fresh coolant

POWER

- 20 CFM vacuum/compressor driven by 8 hp electric start Honda gas engine – 125 psi max



HOSES & REELS

- (1) 1 in in x 50 ft (2.54 cm x 15.2 m) used oil hose on spring retractable reel
- (3) 3/4 in x 50 ft (1.905 cm x 15.2 m) fresh oil hose on spring retractable reel
- (1) 5/8 in x 50 ft (1.6 cm x 15.2 m) fresh coolant hose on spring retractable reel

SAGE OIL VAC ATTRIBUTES

- Patented vacuum process to load fresh fluid tanks (Barrel Straws priced separately — specify quantity and length)
- Patented used Filter Receptacle
- Patented Filter Stinger (priced separately)
- 25 micron filters on all new oil reels

HOSE ENDS, METERS, HANDLES

- Used oil hose — 1 in (2.54 cm) cam and groove fitting
- Fresh fluid hoses — 1/2 in (1.27 cm) flush face quick disconnects, adaptable to meters (priced separately, specify quantity and type)

FRAME

- Tandem leaf spring axle with electric brakes
- Universal 2 5/16 in hitch
- Drop leg jack
- DOT-approved light package
- 7 plug electric adapter

DIMENSION & WEIGHTS

- Length: 192 in (4.8 m)
- Empty weight: 5960 lb (2703 kg)
- Normal max operating weight: 8150 lb (3697 kg)